



Ductile Iron Bench Vises

- Made of ductile iron which is lighter yet 3 times stronger than ordinary cast vises
- 60,000 PSI
- Serrated jaws offer a secure and strong hold
- Precision lead screw threads ensure maximum clamping strength

Mechanics' Vises

Part No.	Jaw Width (inches)	Jaw Opening (inches)	Jaw Depth (inches)	Base Diameter (inches)	Overall length (inches)	Overall Height (inches)	Net Weight (lbs.)
VS3A	4.0	4 ¹ / ₅	2 ³ / ₄	6.0	13 ¹ / ₅	6 ² / ₃	23.3
VS4A	4.5	4 ⁵ / ₇	2 ³ / ₄	6.3	13 ⁴ / ₇		24.9
VS5A	5.0	5 ¹ / ₃	3 ¹ / ₃	6.5	17.0	7 ¹ / ₂	32.1
VS6A	6.0	6 ¹ / ₂	3 ³ / ₄	6.8	19.0	8 ¹ / ₃	43.7
VS8A	8.0	8 ² / ₃	4 ¹ / ₇	7.8	19 ² / ₃	9.0	54.1



Fibre Grip Jaws*

Part No.	Size	Fits Part No.
VS3-FGJAWA	4"	VS3A
VS4-FGJAWA	4 ¹ / ₂ "	VS4A
VS5-FGJAWA	5"	VS5A
VS6-FGJAWA	6"	VS6A
VS8-FGJAWA	8"	VS8A

*Sold in pairs of 2, non magnetic



Swivel Bases

Part No.	Diameter	Mounting Bolt Hole Diameter, in.	Net Weight (lbs.)	Fits Part No.
SWB3A	6.50"	0.43	3.30	VS3A
SWB4A	6.75"	0.43	3.35	VS4A
SWB5A	7.00"	0.53	3.86	VS5A
SWB6A	7.25"	0.53	4.19	VS6A
SWB8A	8.75"	0.53	5.84	VS8A