# AIR CONDITIONER

#### Mobile 3-in-1 Air Conditioner

- Control panel with LED display on unit and remote control included
- 3-in-1 System (A/C, Fan and dehumidify)
- Equipped with casters
- 24 hour timer
- Self-evaporative system
- 3 fan and cooling speeds
- · Window kit included
- Type: Portable

Model No. EA830

Voltage	115 V
Frequency	60 Hz
BTU Rating	12,000
Width	17-1/3"
Depth	12-4/5"
Height	27-1/3"



## DEHUMIDIFIER

### **Dehumidifier**

- · Water bucket full indicator
- Omni-directional casters
- 24-hour timer
- · Auto restart function and auto defrosting
- Energy-Star Certified
- Washable filter
- LED display



Capacity	70 pt.
Tank Capacity	6 L

# LIGHT INDUSTRAIL-DUTY FANS

### **Light Industrial Pedestal and Wall Mount Fans**

- Two speed, 120 V motor
- All-metal construction, chrome grill stand and base painted black
- Pedestal models feature adjustable height and heavy-duty base for added stability
- Can be used in oscillating or non-oscillating mode
- 6' SJT type power cord
- Stem length for pedestal: 35" 48-3/4"
- Arm length wall: 12-5/8"

Model No.	Description	Base Dia.	НР	CFM High	CFM Low
OSCILLAT	ING				
EA282	26" Pedestal	23-3/5"	1/4	7525	4050
EA283	30" Pedestal	27"	1/3	8775	6780
EA284	26" Wall Mount	-	1/4	7525	4050
EA654	30" Wall Mount	-	1/3	8775	6780
NON OSC	ILLATING				
EA657	26" Pedestal	23-3/5"	1/4	7500	6060
EA571	30" Pedestal	27"	1/3	8000	7000
EA655	26" Wall Mount	-	1/4	7500	6060
EA656	30" Wall Mount	-	1/3	7000	8000



# INDUSTRIAL-DUTY FAN

### **Industrial-Duty Air Circulating Fans**

- Two speed, 120 V motor
- · Fully enclosed motor
- All-metal construction
- Stem length for pedestal: 35" 48-3/4"
- Pedestal models feature adjustable height and a heavy-duty round base for added stability
- Can be used in oscillating & non-oscillating modes
- 9.8' SJT power cord

Mardal		<b>D</b>			CEM	CEM
Model No.	Description	Base Dia.	НР	Voltage	CFM High	CFM Low
OSCILLA	TING					
EA643	24" Pedestal	23-3/5"	1/4	120	11,800	7760
EA647	30" Pedestal	27"	1/3	120	13,200	6700
EA645	24" Wall Mount	-	1/4	120	11,500	7680
EA649	30" Wall Mount	-	1/4	120	10,780	7760
NON-OS	CILLATING					
EA642	24" Pedestal	23-3/5"	1/4	120	11,800	7760
EA646	30" Pedestal	27"	1/4	120	10,780	7440
EA644	24" Wall Mount	-	1/4	120	11,500	7680
EA648	30" Wall Mount	-	1/4	120	10,780	7440



## HEAVY-DUTY OSCILLATING FANS

#### **Heavy-Duty Oscillating Pedestal Fan**

- · Fully enclosed motor
- · All-metal construction, chrome grill and base painted black
- Adjustable height and heavy-duty round base for added stability
- Can be used in oscillating or non-oscillating mode
- 9.8' SJT power cord

CFM

No. of Speeds

Fan Dia.

Base Dia.

**Overall Height** 

Model No. EA666



#### **Heavy-Duty Oscillating Wall Fan**

- · Fully enclosed motor
- All-metal construction, chrome grill and base painted black
- Oscillating Angle: 85 degrees
- · 9.8' SJT power cord


CFM

No. of Speeds

Fan Dia.

Base Dia.

Model No. EA667



Decil LATING	Q	MICTING	LANC

1/3

13,200

3

30"

27-1/3"

65" - 78"

### **Outdoor Oscillating Pedestal Fan**

- Enclosed/Waterproof motor type
- · All-metal construction, chrome grill stand and base painted black
- · Feature adjustable height and heavy-duty round base for added stability
- 9.5' power cord with UL GFCI plug

Model No. EA779



### **Misting and Oscillating Pedestal Fan**

- Enclosed/Waterproof motor type (IP44)
- · All-metal construction, chrome grill stand and base painted black
- Pedestal models feature a misting hub, adjustable height and heavy-duty round base for added stability
- · 9' power cord with UL GFCI plug



			- 1		
HP	1/7			HP	1/7
CFM	3780 - 5470 - 7200			CFM	3780 - 5470 - 7200
No. of Speeds	3			No. of Speeds	3
Fan Dia.	30"			Fan Dia.	30"
Base Dia.	27"	16.00		Base Dia.	27"
Overall Height	62" - 76-3/4"			Overall Height	65" - 78"
Watts	220			Watts	220

# HIGH VELOCITY FANS

### 20" High Velocity Pedestal Fan

3850 - 4550 - 5950

3

20" 48" - 60"

120

- All-metal construction, chrome grill, black painted base
- Adjustable pedestal height
- · Head tilting capability of 360°
- 6' SJT type power cord

Model No. EA289

CFM

Fan Dia.

No. of Speeds

**Overall Height** 



#### 24" Roll-About Fan

- · Open motor
- Cart-mounted fan for increased air circulation and optimal mobility
- Cart and frame configuration provides stable quiet operation
- Can be tilted/positioned to maximize ventilation
- 9.8' SJT power cord

Model No. EA476



HP	1/5
CFM	7040 - 7770 - 10,760
No. of Speeds	3
Fan Dia.	24"
Overall Height	54-1/3"
Volts	120

## FLOOR FANS

### **High Velocity Floor Fan**

• Copper motor for longer lifetime

All-metal construction Vertical tilting head

Model No. EA661



HP	1/5			
No. of Speeds	3			
CFM	4000 - 4400 - 4900			
Fan Dia.	20"			

#### **Floor Fans**

- 3-speed, 120 V/60 Hz, 1/4 HP motor
- · All-metal construction
- · Chrome finish
- Vertical tilting head



Model		CFM	CFM	CFM
No.	Diameter"	High	Med	Low
EA528	16	2370	2050	1730
EA290	18	4725	3850	2975

### Rechargeable Indoor/Outdoor Fan with USB port

- Includes a lithium-ion battery and charger cable
- Power indicator light equipped with 5 LED lights to indicate the battery gauge in every 20%
- This fan has a variable speed setting
- USB charging port on the control box can be used to recharge digital devices
- The fan can pivot forwards to a range of 30° and backwards to a range of 90°
- Fan can be used in both indoor and outdoor conditions
- Re-Charge time: 4-5 Hrs
- USB: 5 V, 1 A

Battery Life	4 - 24 hrs
RPM	1700
CFM	1600
No. of Speeds	3
Fan Dia.	12"
Power	25 W
Volts	24



## INDUSTRIAL DRUM FANS

### **Light Industrial Drum Fans**

- two speed, 120 V/60 Hz
- · Open motor type
- All-metal construction, painted black
- 6' SJT type power cord
- 6" casters and easy moving handle



Model No.	Diameter"	НР	CFM High	CFM Low
EA286	28	2/5	8050	6650
EA288	36	3/5	11 200	9100

### **Light Industrial Direct-Drive Slim Drum Fan**

- · Open motor type
- All-metal construction, painted black
   & chrome with aluminum blades
- 360° vertical tilt angle
- 6' SJT power cord
- 5" casters and easy-moving handle
- Weight: 25.09 lbs.

Model No. EA778



HP	3/10
CFM	4500 - 6000 - 7700
No. of Speeds	3
Fan Dia.	24"
Watts	215
Volts	120

# OSCILLATING WALL FAN

### **High Velocity Oscillating Wall Fan**

- Adjustable vertical tilting fan head
- · Rotating or fixed air direction
- · Sliding switch at front of base

CFM 4000 - 4500 - 4800  No. of Speeds 3  Fan Dia. 20"  Volts 120		
No. of Speeds 3 Fan Dia. 20"		
No. of Speeds 3 Fan Dia. 20"		
No. of Speeds 3 Fan Dia. 20"		
Fan Dia. 20"	CFM	4000 - 4500 - 4800
	No. of Speeds	3
Volts 120	Fan Dia.	20"
	Volts	120



# RECHARGEABLE FAN

### **Oscillating Tower Fan**

- Power: 40 W
- · Wide-angle oscillation
- Stable base
- Diameter: 6"
- No. of Speeds: 3

Model No. EA827






Voltage	120 V
Frequency	60 Hz
Width	9"
Depth	9-5/8"
Height	32"

# LIGHT DUTY FANS

### 20" Box Fans

- Three speed control, 120 V
- This fan is designed to efficiently circulate airflow to reach desired comfort levels with a three speed-settings feature
- Five slim blades
- Fully assembled and ready to use
- Weight: 10 lbs.
- · Top-mounted controls

Model No. EA527



CFM	1600 - 2160 - 2280
No. of Speeds	3
Overall Height	21-1/2"
Volts	120

### 16" Wall Mount Oscillating Fan

- Motor 120 V/55 Hz
- Three speed with Eco mode feature
- · Remote with timer mode included
- Rotating or fixed air direction
- Portable and easy to assemble
- Weight: 9 lbs.



CFM	1220 - 1400 - 1600 - 940 (ECO)
No. of Speeds	3
Fan Dia.	16"
Volts	120

# OSCILLATING FANS

### **Oscillating Pedestal Fan**

- 3-speed push button front control
- Adjustable height
- · Rotating or fixed air direction
- Height: 41" 49"

Model No.	Diameter"	CFM Low	CFM Medium	CFM High
EA658	16	-	-	1300
EA551	18	1600	1800	2100



# DESK FANS

### **Oscillating Desk Fans**

- Three speed push button control
- · Rotating or fixed air direction
- Topple resistant base
- Portable and easy to assemble



Model No.	Diameter"	Max CFM
EA305	12	1000
EA306	16	1300

### 6" Clip-on & Desk Fan

- 2-speed, low and high settings
- Fully assembled and ready for use
- · Convertible clip or desk feature
- Tilting head
- Overall Height: 12"



## INDUSTRIAL FAN FORCED HEATER

#### **Portable Salamander Heater**

- Manufactured for long lasting, this portable heater for warehouses, factories, garages, construction sites, pavilions and other open areas, raise temperature to the desired level gradually for worksite comfort
- Fan Motor Type: Enclosed air over, Ball bearing
- · Adjustable thermostat

Over heat prote	" solid rubber wheels ection o different areas of the s Electric g, fan forced	
Volts	240	
Watts	10,000	
BTU/H	34,121	8

## OIL HEATER

#### **Oil-Filled Heater**

- · 7-fin, oil-filled heater
- Three heat settings provide full comfort and efficient operation
- · Adjustable thermostat
- Built-in over heating protection and tip over switch
- Power cord length: 6'

Model No. EA612



Volts	120
Watts	1500
BTU/H	2050 - 3080 - 5120
Amps	12.5

### **Cermiac Oscillating Heaters**

- 2 heat settings (750W/1500W)
- Optional fan only setting
- · Adjustable Thermostat
- Built-in over heating protection and tip over switch
- · Power cord length: 6'





Model No.	Volts	Max. BTU/H	Overall Dimensions
EB019	240	5200	9.6" H x 6.7" W x 5.0" D
EB020	240	5200	18.5" H x 7.4" W x 6.9" D

# PORTABLE CERAMIC HEATERS

#### **Portable Ceramic Heater**

- Full comfort and efficient operation
- Adjustable thermostat
- · Big carry handle
- · Power Source: Electric
- · Power cord length: 6'

Model No. EA650



Volts	120
Watts	900/1500
BTU/H	2560 - 5200
Amps	6.5/12.5

#### **Portable Ceramic Heater**

- Two heat settings provide full comfort and efficient operation
- Adjustable thermostat
- Convenient carry handle
- Stable metal base with tilt angle
- Overheat protection
- Power Source: Electric
- · Power Cord Length: 6'

Model No. EA785



Volts	120
Watts	750/1500
BTU/H	2600 - 5200
Amps	6.25/12.5


## PORTABLE CONVECTION HEATER

### Portable Fan-Forced Convection Heater

- Two heat settings (1500W & 750W) provide full comfort and efficient operation
- · Adjustable thermostat
- · Wide-angle oscillation
- Tip over safety switch and thermal limit control

Model No. EA597





### **Tilted Heavy Duty Heater**

- Industrial finger proof steel intake/discharge grills
- Durable metal construction
- Adjustable thermostat/energy-saving
- · Power cord length: 6'
- · Carrying handle

Model No. EB021

Volts

Watts

BTU/H

Amps



Volts	120			
Watts	750/1500			
BTU/H	2560 - 5200			
Amps	6.25/12.5			

# PORTABLE FAN-FORCED HEATER

#### **Portable Fan-Forced Utility Heater**

- Two heat settings (1300 W and 1500 W) provide full comfort and economic operation
- · Adjustable thermostat
- · Fan-only setting
- Tip over safety switch
- · Built-in carrying handle with front safety guards
- · Power cord length: 6'

Amps



Model No. EA5	98	DONOT COMPANE AND COMPANE
Volts	120	
Watts	1300/1500	
BTU/H	4435/5120	

#### Portable Fan-Forced/Radiant Utility Heater

- Three heat settings provides full comfort and efficient operation
- · Chrome-plated safety grill
- · Automatic built-in thermostat
- · Ceramic core element
- Tip over safety switch and thermal limit
- Power cord length: 6'

Model No. EA466



Volts	120			
Watts	600/900/1500			
BTU/H	2048/3072/5120			
Amps	5.0/7.5/12.5			

## PORTABLE CERAMIC & COIL HEATERS

#### **Portable Ceramic Heater**

10.8/12.5

- Two heat settings provide full comfort and efficient operation
- Adjustable thermostat
- PTC heating element
- Tip over safety switch and thermal safety fuse
- Power cord length: 6'

Model No. EA599



Volts	120			
Watts	750/1500			
BTU/H	2560/5200			
Amps	6.25/12.5			

### **Portable Open Coil Heater**

- Two heat settings
- Fully adjustable automatic thermostat
- Provide full comfort and efficient operation
- Top mounted handle and controls
- · Safety overload switch
- · Power signal light
- · Grounded plug and controls



Volts	120			
Watts	1000/1500			
BTU/H	3410/5120			
Amps	8.3/12.5			

# HEAVY-DUTY HEATERS

#### **Contractor Heaters**

- · Built-in thermostat
- · Permanently lubricated motor
- · Safety high temperature limit
- Built-in handle/cord storage
- Steel spiral fin brazed to metal sheath elements for maximum heat transfer
- 6' heavy-duty cord



Model No.	Volts	Watts	BTU/H	Amps	Plug Type
EA477	240	5600	19,110	23.34	#6-30P
EA561	240	4800	16,380	20	#6-30P
EB022	240	4000	13,650	20	#6-30P

### **Heavy-Duty Ceiling Mount Heaters**

- · Two heat settings
- Built-in ceiling bracket for easy mounting
- · Rugged heavy-duty industrial heaters
- Ideal for use in storage rooms, workshops, garages, warehousing
- · Automatic fan delay
- Overall dimensions:
   10-5/8" W x 12-1/2" D x 14" H



Model No.	Volts	Min BTU/H	Max. BTU/H	Max. Wattage	Motor
EA532	240	11,300	17,060	5000 W	Open
EA652	240	17,060	25,600	7500 W	Enclosed

# DESK HEATERS & WALL CLOCKS

### **Portable Under Desk Radiant Heater**

- One heat setting (on & off)
- · Thin and lightweight
- · Includes fold-out metal floor stand
- Power light indicator with overheat protection
- Dimensions: 20-1/2" x 16-1/2" x 1"
- Safe to touch surface
- Power cord length: 6



#### **Wall Clocks**

- 12/24 hour display12" diameter round office wall clock
- Glass face
- Black chrome frame
- Batteries required: 1 x AA

Model No. HT072



- 12 hour display
- Batteries required: 1 x AAA
- 12-3/4" diameter round office wall clock
- · Wall mount
- Plastic face
- · Black plastic frame

Model No. 0P237

