

Good. Safe. Yellow.

Klingspor Abrasive Cloth

CS 311 Y ACT

Klingspor Schleifsysteme GmbH & Co. KG
Hüttenstraße 36 · 35708 Haiger · Germany
Fon +49 (0) 2773 922-0 · Fax +49 (0) 2773 922-186
sales@klingspor.de · www.klingspor.de



CS 311 Y ACT



▲ grit side

▼ back side



Grit sizes

12	16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	
				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓													

Structure

Grit	Aluminium oxide
Coating	Open
Bonding	Resin
Backing	Y-Polyester
Production width	1.550 mm
Other	Antistatic, ACT
Delivery form	Short and narrow belts, wide belts

Application

Material	Wood, metal, non-ferrous metals
Application	Calibrate sanding till finishing of solid wood and derived timber product surfaces, especially soft wood
Machines	Wide belt sander, long belt sander, edge belt sander, floor sanding machine

Market segment

Wood industry (e.g. manufacturer of plywood and glulam boards, window construction, door manufacturer, parquet manufacturer...) craft producers (carpenter, carpentries)

Product utility

High-quality abrasive belt with tear resistant, strong polyester backing for a high stock removal rate at the processing of wood and derived timber product surfaces with high load. Moisture and climate resistant (can be washed out until grit P50). Open coated grain, improved ACT-recipe as well as antistatic treatment provide a reduced clogging of the belt and therefore a higher life time, especially in soft wood applications.