

Wide range of accessories available for various applications

Please see "Accessories for Multi Tool" for detailed information on the shape, size, recommended use and material of each blade.

Cutting (plunge cutting)



Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Different from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc.
- The blade can be positioned in twelve different angles to allow easy operation in tight spaces.

Cutting



Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Able to perform long distance push cut.
- The segment shape allows flush cutting.

Sanding



Applications:

Wood sanding, concrete sanding, or paint removal, etc. with a variety range of abrasive papers.

Benefits:

- Able to sand in corners.
- Connectable to vacuum cleaner with optional dust extraction system.

Removing grout/ Cutting tiles



Applications:

Replacing broken wall or floor tile.

Benefits:

- Less amount of dust scattering thanks to oscillating action.
- The segment shape allows flush cutting.

Scraping



Applications:

Removing mortar, tile adhesive, hardened glue, window putty, caulking, paint, etc.

Benefits:

- Low-profile blade with a narrow tip allows easy removal of caulking, window putty, etc.

Battery

Model: BTM50



BL1830:
18V 3.0Ah

BL1815:
18V 1.3Ah



Charger

DC18RC / DC18RA
Charging time
22minutes



DC18SD
Charging time
60minutes



Cordless Multi Tool DTM50ZKX1 / DTM50Z

Battery Capacities	18V Li-Ion
Oscillations Per Minute	6,000 - 20,000 OPM
Oscillation Angle	3.2° total
Circumference	7-1/4" (185 mm)
Overall Length	12-3/4" (324 mm)

DTM50ZKX1 Standard Equipment:

Tool Only. Batteries and Charger Sold Separately. Hex Wrench 5 (783233-9), 3-1/2" BIM Saw Blade (B-21325), 1-1/8" Plunge Saw Blade (B-21353), Sanding Pad (B-21537), Adapter A (196271-6), Adapter C (313249-6), Accessory Tool Box (821538-0), Plastic Carrying Case (141562-0)

DTM50Z Standard Equipment:

Tool Only. Batteries and Charger Sold Separately. Hex Wrench 5 (783233-9), Plunge Saw Blade (B-21381), Adapter A (196271-6), Adapter C (313249-6)

- Variable Speed
- Soft Start
- Built-in Job Light



Cordless Multi Tool DTM50ZKX1 / DTM50Z

Satisfy Professional's Needs



EXTRA VERSATILE

Wide selection of accessories available
for various applications

Oscillating Multi Tool



Compatible with all OIS (Oscillating Interface System) accessories

The standard equipment may vary by country.



When QUALITY & SERVICE COUNTS – Choose Makita

makita.ca



Cutting PVC, FRP pipes



Cutting metals



Wood flush cutting



Wood plunge cutting



Deep plunge cutting



Sanding and polishing various materials



Cutting tiles



Removing mortar, tile adhesive

High operation efficiency

Oscillations per minute: up to 20,000 min⁻¹
Oscillating angle: 3.2°



Multi angle setting



Fully 360° multi angle setting enables users to position accessories in 12 different angles (each 30°) to allow access to tight spaces for optimum maneuverability.



Dust extraction system (Option)



Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.

Battery capacity warning lamp



Blinking red: Battery power is nearly used up.
Solid red: Battery power is used up; battery protection circuit will shut off the power.



Cutting plasterboards



Metal flush cutting



Flush cutting of nails



Routing joints on wall tiles



Corner cutting



Cutting window putty, silicone



Cutting polystyrene, rubber



Scraping floor tiles