

## SUPERFLEX HOSE ASSEMBLIES (GL ASSY)

**Applications:** Fairview's new Superflex multi purpose hose is more flexible than most rubber hoses even at extremely low temperatures. It's light weight and relatively high pressure rating make it ideal for pneumatic hand tool and shop air applications.

RMA Class B oil resistance.

- **REINFORCEMENT:** Spiral High Tensile Yarn
- **COLORS:** Green, Red, Yellow
- **TEMPERATURE:** -65°F to +150°F, -55°C to +65°C
- **WORKING PRESSURE:** 250, 300 P.S.I.
- **PACKAGING:** Loose coils or plastic core reels
- **FITTINGS:** Hose Barbs
- **HOSE END GUARDS:** Available

PART No.	Actual I.D. (IN.)	Hose O.D. (IN.)	Working Pressure (P.S.I.)	Reel / Coil Length (FT.)
GLH-4RED-COIL	1/4	.500	300	500
GLH-4RED-REEL	1/4	.500	300	500
GLH-4YEL-COIL	1/4	.500	300	500
GLH-4YEL-REEL	1/4	.500	300	500
GLH-6RED-COIL	3/8	.625	300	500
GLH-6RED-REEL	3/8	.625	300	500
GLH-6YEL-COIL	3/8	.625	300	500
GLH-6YEL-REEL	3/8	.625	300	500
GLH-8GRN-COIL	1/2	.781	300	500
GLH-8RED-COIL	1/2	.781	300	500
GLH-10GRN-COIL	5/8	.906	250	500

  
**ACCUTEK**  
 Fluid and Air Products

LOW TEMPERATURE RATED

**-65°F**  
 (-54°C)

NOTE: WORKING PRESSURE RATED AT +70°F, +21°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE WORKING PRESSURE.